

LCS Chalkboard surfaces combine an excellent erasability with wear resistance, durability and product lifetime warranty. Our smooth matte finish chalk surfaces will not leave “ghosting” and yield less chalk dust for a cleaner, healthier environment. Proper use and maintenance will keep your board looking like new.

#### **First Use of LCS Chalkboards**

1. If present, remove the protective film.
2. Chalk the entire surface using the long side of the chalk.
3. Erase the board with a latex or felt eraser. Keep the erasers dry and clean them regularly.
4. Clean the surface with clear, warm water. (Use 5% Extran MA 02 or phosphate-containing cleaner in water and rub well with a kitchen sponge when necessary.)
5. Rinse well with clear water and strip/wipe the surface with a good window stripper/squeegee. Allow the surface to dry completely before use.

#### **General Cleaning Instructions for LCS Chalkboard**

1. Erase the board with a latex or felt eraser. Keep the erasers dry and clean them regularly.
2. Clean the surface with clear, warm water. (Use 5% Extran MA 02 or phosphate-containing cleaner in water and rub well with a kitchen sponge when necessary.)
3. Rinse well with clear water and strip/wipe the surface with a good window stripper/squeegee. Allow the surface to dry completely before use. Boards used moderately should be cleaned two to three times a week. Boards used more intensely may require daily cleaning.

#### **Removing Metal Scratches or Stubborn Residue**

1. Clean the surface with clear, warm water. (Use 5% Extran MA 02 or phosphate-containing cleaner in water and rub well with a kitchen sponge when necessary.)
2. Rinse well with clear water and strip/wipe the surface with a good window stripper/squeegee. Allow the surface to dry completely before use.

#### **Recommended Accessories**

Calyx recommends using “pure white” chalk (without a wax surface).